

5-Circuit Load Centers

Indoor & Outdoor

- Compact Size
- Suitable for use as service entrance
- In-line branch circuit design
- Steel or plastic Noryl® enclosures
- Variety of circuit counts



- Single Phase, Three Wire, 120 VAC, 10 kAIC Rated
- UL Listed (Panelboards No. 67)
- 60°C/75°C Conductor Rating
- Suitable for use as Service Entrance Equipment when installed in accordance with the National Electric Code

5-Circuit Load Centers Indoor & Outdoor

Main Ampere Rating	Maximum 1-pole Spaces			Cat. No.	Enclosure	Mounting	Type	Dimensions (inches)		
	1" THQL	1/2" THQP	Total					H	W	D
50	3	5	5	TPM305CTRV	Plastic	Flush/Surface	Indoor	9 7/32	7 1/2	3 15/16
70	5	0	5	TL510RT	Steel	Flush	Outdoor	13 1/4	7 1/2	4

TL510RT



TPM305CTRV




Knockouts


Symbol	A	B	D	W	X
Conduit Size in inches	9/32	-	-	-	-
	-	1/2	1/2	-	-
	-	-	3/4	3/4	-
	-	-	-	1	-
	-	-	-	-	1 1/4
	-	-	-	-	1 1/2

Knockouts

Symbol	B	K
Conduit Size in inches	1/2	-
	-	3/4
	-	1
	-	1 1/4
	-	1 1/2



Mounting provided for universal hubs.



Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions.

GE
41 Woodford Avenue, Plainville, CT 06062
www.geelectrical.com
© 2009 General Electric Company

